





KEW SL9721 - 20/35W

IP65 LED weatherproof batten 20/35 watt selectable power

Application

Multi-purpose commercial or industrial utility applications

Design Specifications

- Rounded shape vandal proof design, robust polycarbonate body and UV stabilized polycarbonate diffuser
- Stainless steel clips & screws, 20mm cable gland entry, IP65 and IK08 rated, sensor and emergency options
- Operating temperature -20 to +40 degree C
- Integral constant current non-dimmable LED driver
- Variable wattage DIP switch, 100%, 75% or 50% setting available
- Dimensions: (LWH) 20 watt 610 x 115 x 75mm, 35 watt 1210 x 115 x 75 mm















Performance

Dimmable Driver - **OPTIONAL** In Built Sensor - **OPTIONAL** Sensor Type - **MICRO**

Technical Specification

Model No.	Description	Input (V)	Power (W)	Lumens (lm)	CRI	Body Colour
SL9721/20W WW	LED VANDALPROOF 20W IP65 3K	240	20	900/1800	80	GREY
SL9721/20W DL	LED VANDALPROOF 20W IP65 5K	240	20	900/1800	80	GREY
SL9721/35W WW	LED VANDALPROOF 35W IP65 3K	240	35	1800/3600	80	GREY
SL9721/35W DL	LED VANDALPROOF 35W IP65 5K	240	35	1800/3600	80	GREY
SL9721/20EM	LED VANDALPROOF 20W IP65 EMERG LITH	240	20		80	GREY
SL9721/35EM	LED VANDALPROOF 35W IP65 EMERG LITH	240	35		80	GREY

Model No.	CCT (K)
SL9721/20W WW	3000
SL9721/20W DL	5000/5000
SL9721/35W WW	3000
SL9721/35W DL	5000
SL9721/20EM	
SL9721/35EM	





Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with SAL Terms and Conditions of sale and all images shown are for illustration purposes only and may vary from the actual colour or finish.


ACCESSORIES INCLUDED - Allen key & screws, PVC cable glands, Suspension brackets, INSTALLATION TYPE - Surface mounted,

Suspended (Suspension kit is required), EMERGENCY OPTIONS, Compliant to AS2293, Emergency classification: D32@C0, D20@C90

(SL 9721/35EM), D50@C0, D25@C90 with Lithium Battery technology (SL9721/20EM) SENSOR OPTIONS Integrated microwave motion sensor, Integrated microwave motion sensor with standBY function

Dimensions

SL9721







Product Images



