



LED SURFACE SPOT SMT9017 - 9W

Unitrek, architectural surface mount profile

Application

Retail or residential interior spaces for feature effects

Design Specifications

- Architectural cylindrical profile
- Aluminium body, colour white or optional black
- High performance COB LED, CRI > 80
- Changeable multi-reflector system
- Integral constant current trailing edge dimmable LED driver
- Beam distribution standard 60 degree, 25 or 40 degree options



Technical Specification

Model No.	Description	Input Voltage (V/AC)
SMT9017WW/WH	LED SPOT 9W ADJUST. SUR. 3K WH	240
SMT9017CW/WH	LED SPOT 9W ADJUST. SUR. 4K WH	240
SMT9017DL/WK	LED SPOT 9W ADJUST. SUR. 6K WH	240
SMT9017WW/BK	LED SPOT 9W ADJUST. SUR. 3K BK	240
SMT9017CW/BK	LED SPOT 9W ADJUST. SUR. 4K BK	240
SMT9017DL/BK	LED SPOT 9W ADJUST. SUR. 6K BK	240

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish.

Dimensions

SMT9017

