



OPAL II SO3800TC - 30W


30 watt dimmable LED Oyster with selectable colour

Application

A perfect choice for apartments, residential or commercial spaces

Design Specifications

- Selectable colour temperature with integral DIP switch, 3000, 4000, 6000K,
- 30 watt integral constant current trailing edge dimmable LED driver (excluding SO3800/40TC/S, SO3800/40TC/EMS)
- Durable powder coated steel body profile, colour white
- Opal polycarbonate diffuser
- High efficiency SMD LED chips, CRI > 80
- Sensor models (SO3800/40TC/S, SO3800/40TC/EMS): Microwave sensor mounting height is 2-4hm, sensor detection range is 1-8mtr radius (adjustable) and the timer range is 10sec- 12min (adjustable) with 360 degree detection visibility.



Performance

Dimmable Driver - **YES**

In Built Sensor - **YES**

Sensor Type - **MICRO**

Technical Specification

Model No.	Description	Input (V)	Power (W)	Lumens (lm)	CCT (K)	CRI
SO3800/40TC	LED OYSTER 30W 3/4/6K WH	240	30	2400/2600/2500	3000/4000/5700	80
SO3800/40TC/S	LED OYST SENSOR 30W 3/4/6K WH	240	30	2400/2600/2500	3000/4000/5700	80
SO3800/40TC/EM	LED OYST EMERG. 30W 3/4/6K WH	240	30	2400/2600/2500	3000/4000/5700	80
SO3800/40TC/EMS	LED OYST EM SENSOR 30W 3/4/6K	240	30	2400/2600/2500	3000/4000/5700	80

Model No.	Body Colour
SO3800/40TC	WHITE
SO3800/40TC/S	WHITE
SO3800/40TC/EM	WHITE
SO3800/40TC/EMS	WHITE

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the

time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish.
Emergency models - (SO3800/40TC/EM, SO3800/40TC/EMS): Compliant to AS2293 LiFePO4 battery

Dimensions

SO3800/40

