



STD TUBELINE DIFFUSE - 9/36W

Conventional LED diffuse battens 9 - 36 watt

Application

Conventional LED interior battens ideal for residential and commercial service spaces

Design Specifications

- Pressed steel base with PVC body
- Large terminal block, easy installation
- Quality white powder coat finish
- High efficiency LED T8 tubes fitted, beam distribution 120 degree, CRI >80, 3000, 4000, 6000K
- Safety fuse installed, emergency with LiFePO4 battery included compliant to AS/NZS2293 and sensor models available
- Dimensions: LWH: (9W) 625 x 65 x 77mm), (18W) 1225 x 65 x 77mm, (2x9w) 625 x 110 x 77mm, (2x18W) 1225 x 110 x 77mm



Performance

In Built Sensor - **OPTIONAL**

Sensor Type - **MICRO**

Technical Specification

Model No.	Description	Input Voltage (V/AC)	Lumens (lm)	Power (W)	CCT (K)	Body Colour
STD/106 CW	LED DIFF. BAT. 9W 600mm 4K	240	700	9	4000	WHITE
STD/106 DL	LED DIFF. BAT. 9W 600mm 6K	240	750	9	6000	WHITE
STD/112 CW	LED DIFF. BAT. 18W 1200mm 4K	240	1400	18	4000	WHITE
STD/112 DL	LED DIFF. BAT. 18W 1200mm 6K	240	1700	18	6000	WHITE
STD/206 CW	LED DIFF. BAT. 2 X 9W 600mm 4K	240	1400	18	4000	WHITE
STD/212 CW	LED DIFF. BAT. TWIN 1200mm 4K	240	2800	36	4000	WHITE
STD/212 DL	LED DIFF. BAT. TWIN 1200mm 6K	240	3000	36	6000	WHITE
STD/206EM2500	LED EMERG. BATTEN 2 X 9W 4K	240	n/a	18	4000	WHITE
STD/212EM2500	LED EMERG. DIFF. BAT. TWIN 4K	240	n/a	36	4000	WHITE



Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish.