



LED STD25 NT

Wide body LED surface mount diffused linear batten

Application

Conventional linear LED batten profile ideal for residential and commercial spaces

Design Specifications

- Durable metal body profile, white powder coat finish in two traditional sizes, twin and single lamp configuration
- Optional (to order separately) choice of 3000,4000,6000K, CRI>80 LED tubes
- Large terminal block, easy installation
- Safety fuse installed
- High performance PMMA prism diffuser, beam distribution 120 degree
- Dimensions: (L x W x H mm) STD25/106 - 620 X 83 X 69mm, STD25/206 - 620 X 83 X 109mm, STD25/112 - 1230 X 83 X 69mm, STD212/NT - 1230 X 83 X 109mm.



Technical Specification

Model No.	Description	Input Voltage (V/AC)	Body Colour	Dimensions (mm)
STD25/106NT	LED DIFFUSED BATTEN 1 X 9W PROFILE NO TUBE	240	WHITE	620(L) x 83(W) x 69(H)
STD25/206NT	LED DIFFUSED BATTEN 2 X 9W PROFILE NO TUBE	240	WHITE	620(L) x 83(W) x 109(H)
STD25/112NT	LED DIFFUSED BATTEN 1 X 18W PROFILE NO TUBE	240	WHITE	1230(L) x 83(W) x 69(H)
STD25/212NT	LED DIFFUSED BATTEN 2 X 18W PROFILE NO TUBE	240	WHITE	1230(L) x 83(W) x 109(H)

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish.