



TUBELINE WIREGUARD STG - 9/36W

Conventional LED bare battens with wire guard protection 9 - 36 watt

Application

Conventional designed bare LED battens with wire guard protection, ideal for commercial interior spaces

Design Specifications

- Pressed steel base with PVC body
- Large terminal block, easy installation
- Powder coated white steel wire guard
- High efficiency LED T8 tubes fitted, CRI > 80, CCT 3000, 4000, 6000K, beam distribution 120 degree
- Safety fuse installed, sensor and emergency models compliant to AS/NZS2293 available
- Dimensions LWH: (9W) 625 x 65 x 77mm, (18W) 1225 x 65 x 77mm, (2x9w) 625 x 110 x 77mm, (2x18W) 1225 x 110 x 77mm



Performance

In Built Sensor - **OPTIONAL**
Sensor Type - **MICRO**

Technical Specification

Model No.	Description	Input Voltage (V/AC)	Lumens (lm)	Power (W)	CCT (K)	Body Colour
STG/106 CW	LED WIRE/G BATTEN 9W 600mm 4K	240	850	9	4000	WHITE
STG/112 CW	LED WIRE/G BATTEN 18W 1200mm4K	240	1750	18	4000	WHITE
STG/206 CW	LED WIRE/G BAT. 2x9W 1200mm 4K	240	1700	18	4000	WHITE
STG/212 CW	LED WIRE/G BAT.2x18W 1200mm 4K	240	3500	36	4000	WHITE
STG/206EM2500	LED EMERG. WIRE GUARD 2X9W 4K	240		18	4000	WHITE
STG/212EM2500	LED EMERG. WIRE GUARD 2X18W 4K	240		36	4000	WHITE

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish.

STB/206EM2500, STB/212EM2500 TUBELINE, Compliant to AS2293, LED charge status indicator, Test switch, Guaranteed 90 minutes emergency operation, Intelligent automatic recharging function, 16 hours charge time, Deep discharge protection, SELV compliant

Product Images

