



NEW BONDI II SL7224TC - 2 x 5W

IP65 LED architectural wall luminaires

Application

A decorative residential exterior or interior solution

Design Specifications

- Aluminium body profile, powder coat black, white or (AST) stainless finish
- Clear tempered glass cover
- Polycarbonate optical lens
- High efficiency LED optics
- Integral non-dimmable LED driver
- Up and Down light distribution 36°

Performance

- Dimmable - NO



Technical Specification

Product	Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	CCT (K)	CRI
	SL7224TC/BK	240	10	370/410/390	3000/4000/6000	80
	SL7224TC/AST	240	10	370/410/390	3000/4000/6000	80
	SL7224TC/WH	240	10	370/410/390	3000/4000/6000	80

Beam Angle (°)	Mass (kg)	Diameter (mm)	Dim (mm)	Body Colour
36	0.37	60	160(H) x 84(D)	BLACK
36	0.37	60	160(H) x 84(D)	ALUMINIUM STAINLESS
36	0.35	60	160(H) x 84(D)	WHITE



NOTE: Lumens (lm) displayed are per optical head

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

Dimensions

SL7224TC

