



STARGEM II WITH SENSOR SES7060 - 2 X 10W

2 x 10 watt wall mount LED floodlight, IP54 with PIR sensor

Application

A versatile security solution for residential exterior spaces

Design Specifications

- Independently adjustable heads
- Robust polycarbonate base
- Opal polycarbonate diffuser, beam distribution 100°
- High efficiency LED optics, non-dimmable LED driver
- Integral infrared motion sensor with override function. To enable 'Manual Override' or 'Permanent On', simply switch off and on twice within six seconds. The lights will now stay on permanently. To return to 'Automatic Mode', switch the unit off and after ten seconds switch on again. The unit will resume normal operation.
- Installation height max 2.5hm, double insulated



Performance

- Dimmable - **NO**
- In Built Sensor - **YES**
- Sensor Type - **PIR**



Technical Specification

Product	Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	CCT (K)	CRI
	SES7060NDL/BK	240	20	1600	5000	80
Beam Angle (°)	Body Colour	Dim (mm)		Mass (kg)		
100	BLACK	240(W) x 188(H) x 165(D)		0.58		

* Lumens shown are TOTAL luminaire Lumen (lm).

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

Dimensions

Sensor Specifications

Power Source	Power	Detection Range	Detection Angle	Detection Motion Speed	Working Temperature	Time Setting	Lux Threshold
240V 50Hz	0.45W (idle 0.1W)	3.2m @ 2.5m height	180°	0.6-1.5 m/s	-10-40°C	10s-4min	10-2000 Lux

