


DECO-20-TRIO Fixed LED Downlight



Description

The DECO-20 and Deco-28 range of commercial LED downlights have been designed with a deep-set frame to reduce glare from the light source. Featuring a wide light distribution, and with an ultra slim housing, allows for this downlight to be suitable for installations where ceiling space is minimal. Complete with a dimmable LED driver and flex and plug. Fully dimmable with Domus dimmer series.

Now with TRIO, the added option of changing the colour temperature output of the downlight with a dip switch at the back of the fitting.




Specification Features


Input Voltage:	240V AC
Power (W):	20W
IP rating (IP):	44*
Lumens (lm):	Warm White 3000K - 1700lm Neutral White 4000K - 1750lm White 5700K - 1800lm
LED type:	SMD
CCT:	3000K - 4000K - 5700K (Switchable)
CRI:	≥80
Beam angle (°):	120°
Dimmable:	Yes**
Lifespan (hrs):	50,000hrs
Cutout (∅):	∅160-170mm

* IP44 rating is from the underside of the down light once installed into the ceiling.

** Tested on the Domus dimmer series. May work on others but not tested.



Diagrams / Additional



Cutout: ∅160 - ∅170mm

Item No.	Variant	Colour Temp
DECO-20-WHT	20432	TRIO
DECO-20-BLK	20433	