

29-31 Richland St. Kingsgrove. Sydney NSW 2208 Australia

Phone: 02 9554 9600 | Fax: 02 9554 9433

enquiries@domuslighting.com.au | www.domuslighting.com.au

## Installation Manual

Date: 01/2019

## EASY-250-RND

Variants	Item No.	Colour Temp
20954	EASY-250-RND-WHT	TRIO


Description: Polycarbonate ceiling light

Thank you for purchasing your new EASY-250-RND Ceiling Light, Please take the time to read and understand the instruction sheet below. Failure to do so may void warranty.


## **Specifications**

Voltage:	240V AC	Lumen (±5%):	Warm White 3000K - 930lm Neutral White 4000K - 965lm White 5700K - 1000lm	Dimmable:	Yes
Power:	10W	Beam Angle:	120°	Operating Temp:	-20°C~45°C
IP Rating:	IP54	CCT:	3000K - 4000K - 5700K	Power Factor:	
CRI:	≥80	Lifespan:	50,000hrs		






2. Press the side push tabs to take



3. Knock-in the plastic anchor into



5. Remove the driver cover and line pressing clip, connect the wires correspondingly.







**Note:** -The lamp must be installed by professional electrician

-Ensure the power supply is switched off before fitting this product

-Do not touch the lamp when in use

-Keep away from hot steam and corrosive gas