

## Installation Manual

## PANEL-312

Order Code	Product Code	Description	
19309	PANEL-312-SLR-W	45W LED PANEL, silver finish - White 6000K	
19310	PANEL-312-SLR-NW	45W LED PANEL, silver finish - Neutral white 4000K	
19311	PANEL-312-SLR-WW	45W LED PANEL, silver finish - Warm white 3000K	

Thank you for purchasing your new LED PANEL-312, Please take the time to read and understand the instruction sheet below. Failure to do so may void warranty.

## **Specifications**

Voltage:	240V AC	Lumen (±5%):	WW 3000K-2950lm NW 4000K-3000lm W 6000K-3050lm	Dimmable:	YES*	
Power:	45W	CCT:	3000K - 4000K - 6000K	CRI:	≥80	
IP Rating:	44	Lifespan:	50,000hrs			
Mounting Type:	Recessed into standard grid ceiling or via optional plaster trim kit for plaster board ceilings or via optional wire suspended or surface mounted kit.					

\* Tested on the Domus dimmer series. May work on other but not tested.





# DOMUS®

## **Installation Manual**

#### **Recessed into ceiling**

1. Remove ceiling plaster slap.






2. Connect power supply.


3. Fix the panel light into the right place.



4. Stabilize the panel.



#### Suspending



- A. Fix the anchor into target place on the ceiling.
  B. Fix the installation mount on the ceiling with plastic anchor.
- Hang the panel to ceiling with suspended installation kits.




3. Adjust the length of steel wire. Connect the power supply.

### **Surface Mounted**

1. Open a suitable size hole in the ceiling.




2. Put the plaster recessed frame into the hole.




3. Fix the plaster recessed frame with the 4pcs clips.



4. Connect power supply with the LED panel light.



5. Put the LED panel light into the plaster recessed frame.



### Surface mounted



2. Pull down the side frame





3. Push the panel into the

frame, connect the driver

- 4. Install the side frame
- 5. Turn on the power switch, finish the installation.



