

STRIP-120 Flexible LED Strip



Description

Introducing STRIP-120 LED strip lighting system. STRIP-120 is the first in the line-up of high performance LED strip lighting in the Domus offering. New possibilities can be realised in the way we illuminate areas and surfaces. The secret lies in its thin and flexible PCB which allows for long and linear lengths to be preformed with ease. With added advantages such as a higher number of SMD LEDS over a smaller area STRIP-120 gives that almost seamless continuous line of light with no visible spotting.



Order Info

Specification Features

Colours: Light Source: LED Type: Colour Temperature (K): Colour Rendering Index:	3 colour options available 3020 SMD LED Epistar (Taiwan) 3200K, 4000K, 6500K ≥83	Colour Temp: Order Code: Product Code: Lumens/m:
Number of LED per mtr: Wattage Per MTR (W): Input Voltage (VDC): Beam angle (°):	120 19.2W 12VDC 120° Parallel	Colour Temp: Order Code: Product Code: Lumens/m:
Wiring: IP Rating: Cutting Increments/Sections: Requires: Dimmable:	IP20 25mm (group of 3 LED) 12VDC constant voltage driver Yes* DALI, 0-10V, DMX-512, RF	Colour Temp: Order Code: Product Code:
IES files: Mounting:	Yes** Optional aluminium mounting profile***	Lumens/m:

4000K lour Temp: der Code: 20008 oduct Code: STRIP-120-40K mens/m: 1476 lm/m

lour Temp: der Code: oduct Code: mens/m:

3200K 20020 STRIP-120-32K 1322 lm/m

6500K


20019

STRIP-120-65K

1497 lm/m

Diagrams / Additional


** Available upon request.



For dimming options please refer to the controller section for further details.

*** Due to the nature of this LED strip light, the use of a aluminium mounting

profile in mandatory for heat dissipation (not included).



Domus Lighting 29-31 Richland Street. Kingsgrove NSW 2208 | Phone: (02) 9554 9600 | Fax: (02) 9554 9433 | email: sales@domuslighting.com Specification subject to change without prior notice.