DOMUS®

Installation Manual

TAB-300

| Variant | Item No. | Description | |
|---------|-------------|---|--|
| 19558 | | Square slimline ceiling light, Satin white - Warm White 3000K | |
| 19559 | TAB-300-WHT | Square slimline ceiling light, Satin white - White 5000K | |
| 19560 | | Square slimline ceiling light, Silver - Warm White 3000K | |
| 19561 | TAB-300-SLR | Square slimline ceiling light, Silver - White 5000K | |

Thank you for purchasing your new LED TAB-300, Please take the time to read and understand the instruction sheet below. Failure to do so may void warranty.

Specifications

| Voltage: | 240V AC | Lumen (±5%): | Warm White: 2700lm White: 2850lm | Dimmable: | Yes* | | |
|---|---------|--------------|-------------------------------------|-----------|-----------|--|--|
| Power: | 30W | Beam Angle: | 180° | Lifespan: | 40,000hrs | | |
| IP Rating: | 54 | CCT: | 3000K - 5000K | CRI: | ≥83 | | |
| * Tested on the Denne dimension Manuscription others but not to the d | | | | | | | |

* Tested on the Domus dimmer series. May work on others but not tested.

Steps:

- Please make a visual inspection of the fixture prior to installation. If any defects are to be found please return to your place of purchase for a replacement.
- Make sure all power is turned off from the mains switch board prior to removing or installing a new fixture.
- Please install the supplied mounting bracket. This will be located on the rear of the product and held into place with grub screws.
- When installing the bracket please use correct screws to suit the surface into which you are mounting to. (The provided screws are general purpose and may not suit the application).
- Once mounted please remove the terminal block cover located on the rear of the luminaire. Proceed in making the electrical connection in accordance with Australian standards.
- After connection has been made please proceed in installing the fixture back into place. Please tighten the grub screws and ensure fitting is securely mounted.
- Please turn on the mains power and check the fixture to make sure all is in working order.
- To ensure the appearance of your new fixture it's advised that you clean the fixture at least every 12mths with fresh clean water and a mild soap.



