

29-31 Richland St. Kingsgrove. Sydney NSW 2208 Australia

Phone: 02 9554 9600 | Fax: 02 9554 9433

enquiries@domuslighting.com | www.domuslighting.com

Installation Manual


Date: 10/2018 **ZAC-4-RND**

Variant	Item No.	Description	
19727	ZAC-4-RND-BLK-WW	LED recessed wall light, black finish. 3000K, warm white.	
19728	ZAC-4-RND-BLK-W	LED recessed wall light, black finish. 5000K, white.	
19729	ZAC-4-RND-DGR-WW	LED recessed wall light, dark grey finish. 3000K, warm white.	
19730	ZAC-4-RND-DGR-W	LED recessed wall light, dark grey finish. 5000K, white.	
19731	ZAC-4-RND-SLR-WW	LED recessed wall light, silver finish. 3000K, warm white.	
19732	ZAC-4-RND-SLR-W	LED recessed wall light, silver finish. 5000K, white.	
19733	ZAC-4-RND-WHT-WW	LED recessed wall light, white finish. 3000K, warm white.	
19734	ZAC-4-RND-WHT-W	LED recessed wall light, white finish. 5000K, white.	

Thank you for purchasing your new LED ZAC-4-RND, Please take the time to read and understand the instruction sheet below. Failure to do so may void warranty.

Specifications

Voltage:	240V AC	Lumen (±5%):	Warm White 3000K - 200lm White 5000K - 250lm	Dimmable:	No		
Power:	4W	Beam Angle:	30°	Operating Temp:	-20°~45°		
IP Rating:	IP65	CCT:	3000K - 5000K	Power Factor:			
CRI:	≥80	Lifespan:	50,000hrs				



Cutout without recessed box: (Ø) 100mm Cutout with recessed box: (Ø) 110mm

⁻Keep away from hot steam and corrosive gas